

(54) CUTTING TOOL MADE OF SURFACE-COATED WC-BASE SINTERED
HARD ALLOY

(11) 6-10S254 (A) (43) 19.4.1994 (19) JP

(21) Appl. No. 4-282556 (22) 28.9.1992

(71) MITSUBISHI MATERIALS CORP (72) AKIRA OSADA(1)

(51) Int. Cl.⁸. C23C16/30, B23B27/14, B23P15/28

PURPOSE: To provide a cutting tool showing excellent cutting performance, on the surface of a WC-base sintered hard alloy substrate, by forming a specified titanium nitride internal layer and a specified titanium carbo-nitride external layer thereon.

CONSTITUTION: A titanium nitride internal layer having 5 to 50nm thickness and whose crystalline grains have a granular structure is formed on the surface of a WC-base sintered hard alloy substrate. On the titanium nitride internal layer, a titanium carbo-nitride external layer having 1 to 8 μ m thickness and whose crystalline grains have a columnar structure is formed. On the surface of the cutting tool made of the surface coated WC-base sintered hard alloy, furthermore, a single layer or multi layers of one or two kinds among aluminum oxide, titanium carbonate and titanium carbo-nitride-oxide having a 0.1 to 2 μ m thickness. In this way, the surface coated cutting tool in which the peeling of the hard coated layer is hard to occur can be provided.